



MBSP48-12



## MBSP SERIES

### Sandwich/Salad Prep Units

#### MODELS

- MBSP27-8
- MBSP36-10
- MBSP48-12
- MBSP60-16
- MBSP72-18

### FEATURES

#### CONSTRUCTION

- Curved corner design creates a stylish appearance and reduces chances of injury in slip-and-fall accidents
- Stainless steel interior and exterior
- Foamed-in-place with low ODP polyurethane insulation
- Standard 9 1/2" deep reversible cutting board
- Insulated top lid
- Wall thickness: 1.77"
- 6" diameter casters
- Adjustable heavy-duty vinyl-coated shelves
- 1/6 size pans included (two 1/9 size pans and six 1/6 pans included in MBSP27-8)

#### DOORS

- Self-closing
- Standard door swing configuration:
  - 1-door models ..... hinged right
  - 2-door models . left hinged left, right hinged right
  - 3-door models . left hinged left, middle hinged left, right hinged right
- Door width:
  - MBSP27-8 ..... 27 1/4"
  - MBSP36-10 ..... 18"
  - MBSP48-12 ..... 23 7/8"
  - MBSP60-16 ..... 30"
  - MBSP72-18 ..... 23 7/8"

#### REFRIGERATION

- Self-contained forced air refrigeration system
- Refrigerant: R-134a
- Temperature range: 32° to 40°F (0° to 4°C)

#### WARRANTY

- Standard limited four year extended compressor and one year limited parts and labor

### OPTIONS

- Single or double overshelf
- Refrigerated drawers (excluding MBSP36-10)

### BID SPECIFICATIONS

Item no. MBSP-\_\_\_\_\_. Provide \_\_\_\_\_ Sandwich/Salad Prep Unit(s), Master-Bilt model no. MBSP\_\_\_\_\_.

Prep unit will feature rounded corner construction with stainless steel interior

and exterior.

The refrigeration system will be bottom mounted and self-contained. Refrigerant will be R-134a. The temperature range will be 32° to 40°F (0° to 4° C).


Prep unit to have standard limited 4 year extended compressor warranty and one year limited parts and labor warranty.

Prep unit to be UL, C-UL and ETL Sanitation listed.


### TECHNICAL SPECIFICATIONS

MODEL	DIMENSIONS (in.)			DIMENSIONS (mm)			VOLTS	AMPS	UNIT H.P.	NO. OF DOORS	NO. OF SHELVES	NO. OF PANS	CAP. CU. FT.	SHIP CU. FT.	SHIP WT. (LB/KG)
	L	D	H*	L	D	H*									
MBSP27-8	27 <sup>1</sup> / <sub>2</sub>	30	42 <sup>1</sup> / <sub>2</sub>	699	762	1080	115	3.2	1/5	1	1	(6) 1/6, (2) 1/9	6.8	24.9	212/96
MBSP36-10	36 <sup>3</sup> / <sub>8</sub>	30	42 <sup>1</sup> / <sub>2</sub>	924	762	1080	115	3.6	1/5	2	2	(10) 1/6	9.4	31.4	268/122
MBSP48-12	48 <sup>1</sup> / <sub>4</sub>	30	42 <sup>1</sup> / <sub>2</sub>	1226	762	1080	115	7.9	3/8	2	2	(12) 1/6	12.7	42.5	304/138
MBSP60-16	60 <sup>3</sup> / <sub>8</sub>	30	42 <sup>1</sup> / <sub>2</sub>	1534	762	1080	115	7.9	3/8	2	2	(16) 1/6	16.0	52.4	344/156
MBSP72-18	72 <sup>3</sup> / <sub>8</sub>	30	42 <sup>1</sup> / <sub>2</sub>	1838	762	1080	115	9.9	3/8	3	3	(18) 1/6	19.6	61.8	384/175


\*Height includes casters.




MBSP27-8  
PLAN VIEW




MBSP36-10  
PLAN VIEW




MBSP48-12  
PLAN VIEW



MBSP60-16  
PLAN VIEW




MBSP72-18  
PLAN VIEW




MBSP27-8  
ELEVATION VIEW




MBSP36-10  
ELEVATION VIEW




MBSP48-12  
ELEVATION VIEW



MBSP60-16  
ELEVATION VIEW



MBSP72-18  
ELEVATION VIEW




ALL MODELS  
SIDE VIEW

### LISTINGS



### HOOKUP

All models via plug in, 9 foot long flexible three wire 14/3 cord with molded plug.



NEMA 5-15P

NOTE: Cabinet designed for optimum performance in air-conditioned area at 75°F ambient and 55% relative humidity. All specifications subject to change without notice.